

Containment Accessories - Drop Away Panel

SKU#: ECX-DP-061260-F, ECX-DP-061380-F, ECX-DP-061870-F, ECX-DP-061990-F

The Enconnex containment drop away system is a quick and low cost solution for cold aisle containment. It will separate cold and hot air for more efficient cooling and, in the event of a fire, the ceiling panels will shrink and drop away providing unobstructed sprinkler coverage.

PRODUCT APPLICATIONS

- Data Centers
- High-Density Applications
- Energy Rebate Programs

PRODUCT FEATURES

- Low cost and quick installation
- Can cut on site to fit with variable site situation.
- Fire rating Class A Vinyl
- Meets National Fire Protection Association (NFPA 13) standards
- No need to integrate with BMS
- L shape frame overlap for sealing



Figure 1: Drop Away Panel



Figure 2: Drop Away Panel

PHYSICAL SPECIFICATIONS

PHYSICAL	ECX-DP-061260-F	ECX-DP-061380-F	ECX-DP-061870-F	ECX-DP-061990-F
Dimensions*	49.6" x 23.6" x 1.0" (1260 x 600 x 25 mm)	54" x 23.6" x 1.0" (1380 x 600 x 25 mm)	73.6" x 23.6" x 1.0" (1380 x 600 x 25 mm)	78.3" x 23.6" x 1.0" (1990 x 600 x 25 mm)
Net Weight	12 lbs (5.5 kg)	14 lbs (6.4 kg)	18 lbs (8.2 kg)	20 lbs (9.1 kg)
Shipping Dimensions	50.7" x 24.7" x 10.4" (1288 x 628 x 264 mm)	55.1" x 24.7" x 10.4" (1401 x 628 x 264 mm)	74.7" x 24.7" x 10.4" (1401 x 628 x 264 mm)	79.4" x 24.7" x 10.4" (1401 x 628 x 264 mm)
Shipping Weight	125 lbs (56.8 kg)	145 lbs (66 kg)	185 lbs (84 kg)	210 lbs (95 kg)
Aisle Width	1200 mm, 4 ft, DC cabinet	1200 mm, 4 ft, SSG cabinet	1800 mm, 6 ft, DC cabinet	1800 mm, 6 ft, SSG cabinet
Color*	Clear frame, frosted panel			
Shipping	10 pcs. per pallet			
Fire Rating	Class A & Flame V0			
Toolless Mounting	Velcro	Velcro	Velcro	Velcro

^{*} Can customize accordingly, please contact Enconnex Engineering

