

# Input Metered, Outlet Switched PDU

ECX-SV1212121-P



[www.enconnex.com](http://www.enconnex.com)

+ 1 (833) TALK ECX

[sales@enconnex.com](mailto:sales@enconnex.com)

The ECX-SV1212121-P input metered, outlet switched PDU distributes power to devices in the rack and offers real-time phase and circuit breaker metering with network monitoring of power loads for overload avoidance, capacity & load balancing, and energy use optimization. Switched outlets allow power-up equipment sequencing, remote reboot, and outlet access control. A hot-swappable network management control allows for future upgrade and enhanced MTTR. Up to 8 optional environmental sensors and security access handles can be connected and managed through the PDU. ECX-SV1212121-P can be monitored through the embedded webUI, telnet, SNMP, or SSH interfaces.

## PRODUCT FEATURES

- Outlet access control
- Power sequencing
- Premium high temperature branch rated magnetic hydraulic circuit breaker
- Ultra-Low-profile design
- Alternate-branched outlets
- High Density outlet arrangement
- Real-time face and circuit breaker metering and monitoring of power loads
- Remote PDU access management
- Environmental monitoring to detect temperature, humidity and water leaks (up-to eight sensors)
- Consolidation of IP address management by daisy-chain of up to four PDU's
- Conforms to the following standards: Redfish API, RESTful API, IPV6 -SSL/IPsec, SNMP V3
- Integrates with DCIM and BMS

## APPLICATIONS

- Environments that require power sequencing
- Colocation facilities
- MDF, IDF, Data Center, Computer Room, Data Room Environment



## SPECIFICATIONS

PDU FUNCTION	SPECS
Energy Metering	Voltage (V), Current (A), Active Power (kW), Apparent Power (kVA), Energy (kWh), Power Factor
Metering Accuracy	Billing grade, 1% ISO/IEC 62053-21
Outlet Level Metering	(V, A, kW, kVA, kWh, pf) per ISO/IEC 62053-21
Outlet Switching	Yes, with user programmable startup sequencing
Network Management	Gigabit, 10/100/1000 BaseT
Locking IEC Outlets	Yes, dual methods – Wlock and cable tie downs
Color Coded Outlets and Circuit Breakers	Yes
Field Replaceable Intelligence Module	Yes, full hot-swappable

ELECTRICAL	SPECS
Acceptable Input Voltage	230 VAC, +6%, -10%
Input Current (Phase)	32A
Input Frequency	50 Hz
Input Power	7.36 kVA
Input Plug	IEC 60309 332P6 (IP44)
Rated Output Current (Phase)	32A
Rated Output Current (Outlet)	C13: 10A, C19: 16A
Overload Protection (Internal)	(2) 16A, 1-pole 5kAIC hy-mag circuit breakers
Outlet Configuration	Total: (12)C13, (12)C19; Per Breaker: (6)C13, (6)C19

PHYSICAL	SPECS
Dimensions	58.7" x 2.05" x 2.09" in (1491 x 52 x 53 mm)
Depth at Circuit Breaker, in (mm)	N/A
Input Cord Length, ft (m)	10' (3m)

ENVIRONMENTAL	OPERATING	STORAGE
Maximum Elevation, Above MSL	0-10,000 ft / 0-3,000 m	0-50,000 ft / 0-15,000 m
Temperature	23 to 140°F / -5 to 60°C	-13 to 149°F / -25 to 65°C
Humidity	5-95% RH non-condensing	5-95% RH non-condensing

COMPLIANCE/STANDARDS	SPECS
EMC Compliance	N/A
Safety Compliance	UL, cUL, IEC/UL 60950-1, UL/IEC 62368-1, CE-LVD
Environmental	RoHS

WARRANTY	SPECS
PDU Warranty	5 years