

# FW Series Cabinet

SKU#: ECX-FW-61242-CO



[www.enconnex.com](http://www.enconnex.com)

[sales@enconnex.com](mailto:sales@enconnex.com)

The Enconnex FW Series server cabinet is the ultimate solution designed and engineered for demanding data center environments.

## PRODUCT FEATURES

- Solid tube steel construction provides some of the best load ratings in the industry
- Recessed PDU mounting rail design makes server maintenance quick and easy
- Quad side panel design makes accessing the side of your equipment convenient
- Standard no-doors design allows for maximum access while reducing footprint
- Modular roof panel with large cable pass-through for oversized cable bundles
- Adjustable equipment rails with numbered labeling on both sides
- 3" casters make rolling a loaded cabinet smooth and simple

## PRODUCT BENEFITS

- Engineered to make equipment installation simple
- No-door design allows for better access and a smaller footprint
- Can be easily bundled with containment options to create hot/cold aisle solution
- Full range of accessories to meet your airflow and cable management needs

## INCLUDED EQUIPMENT

- Solid tube steel, six post open frame
- Dual side panels (4 per complete cabinet)
- Optional perforated doors are available
- Modular roof with snap-in grommets
- Equipment mounting rails, adjustable, with hardware
- Two(2) PDU mounting bars at rear side of the cabinet
- Leveling feet and 3" high performance casters
- Two (2) adjustable cable management bars

## SEISMIC SPECIFICATIONS

**Standard Cabinet** Our standard cabinet can be configured with a Zone 4 mounting kit and bayin kit to meet current Zone 4 compliancy in seismic areas.

**Seismic Cabinet** Our seismic cabinets are engineered to meet current GR-63-CORE, NEBS seismic standards. These cabinets are manufactured with a welded design to ensure structural rigidity in seismic areas.



## PRODUCT SPECIFICATIONS

<b>Cabinet Style</b>	Floor Standing
<b>Physical Dimensions (WxDxH)</b>	600 x 1219 x 1956mm
<b>Casters</b>	3" High-Grade
<b>UL Rating</b>	60950
<b>Height</b>	42U
<b>RoHS/ELV Compliance</b>	RoHS Compliant, ELV Compliant
<b>NOM</b>	EP Tested for NOM Compliance
<b>Approvals</b>	EIA/ECA-310-E
<b>Colors</b>	Black
<b>WeightCapacity-Stationary(lbs)</b>	5000
<b>Weight Capacity - Rolling (lbs)</b>	4000
<b>Units per pallet</b>	1

