

Notes/Instructions:

REV	REV DATE	DESCRIPTION	APPROVAL
A	2019-06-19	RELEASE	

NOTES:

1. INTERNAL WIRING:

WIRE TYPE:

LINE 1/R/X COLOR:

EARTH GROUND COLOR:


NEUTRAL WIRE COLOR:

UL AWM 1015, 10 & 12 & 18AWG

BROWN

GREEN/YELLOW STRIPE



BLUE



INTERNAL WIRING SCHEMATIC

Notes:

This drawing and its specifications are the property of ENCONNEX and shall not be copied, reproduced, or used in whole or in part, as the basis for the manufacture or sale of items without written permission from ENCONNEX. This drawing is based upon the latest available information and is subject to change without notice.

TOLERANCES LINEAR (mm) X = ± 1 X.X = ± 0.5 X.XX = ± 0.30 X.XXX = ± 0.130 ANGULAR X = 1° .X = 0.5° .XX = 0.25°	MATERIAL:	 4670 AIRCENTER CIRCLE, RENO, NV 89502	PART NUMBER: ECX-WV1220040-P
	DESCRIPTION:		DESCRIPTION: Wiring Scheme
	DEBUR AND BREAK SHARP EDGES/CORNERS AT 0.2mm MAX	DRAWN BY: Jing Zhang	ORG DATE: 2019-06-19
	UNITS: mm [in]	APPROVED BY: R. FAULKNER	REV DATE:
	INTERPRET TO ASME Y14.100	SIZE: A4	SCALE: 1 : 1
		SHEET: 2/2	REV: A