




Notes/Instructions:

MPO TO MPO 50/125 OM3 YOFC 24 CORE FIBER OPTIC CABLE

REV	REV DATE	DESCRIPTION	APPROVAL
A	2021-07-20	RELEASE	Mike



Fiber Mapping:


MPO 24 CORE	Fiber color	MPO 24 CORE
1	Blue	13
2	Orange	14
3	Green	15
4	Brown	16
5	Gray	17
6	White	18
7	Red	19
8	Black	20
9	Yellow	21
10	Purple	22
11	Pink	23
12	Aqua	24
13	Blue	1
14	Orange	2
15	Green	3
16	Brown	4
17	Gray	5
18	White	6
19	Red	7
20	Black	8
21	Yellow	9
22	Purple	10
23	Pink	11
24	Aqua	12

Specifications:

Fiber Mode	MM
Type	MPO TO MPO
Cable Diameter(mm)	φ 3.0
Cable Color	Aqua
Core Diameter(um)	50/125
Insertion Loss(dB)	≤0.60
Return Loss(dB)	≥ 20
Operating Temperature(℃)	-20~+70
Storage Temperature(℃)	-20~+70


Length Tolerance:

Length(M)	Total Length Tolerance
L≤1	+5CM/-0
1<L≤10	+10CM/-0
10<L	+L1%/-0



Notes:

This drawing and its specifications are the property of ENCONNEX and shall not be copied, reproduced, or used in whole or in part, as the basis for the manufacture or sale of items without written permission from ENCONNEX. This drawing is based upon the latest available information and is subject to change without notice.

TOLERANCES LINEAR (mm) X => 1 .X => 0.5 .XX => 0.30 .XXX => 0.130 ANGULAR X = 1° .X = 0.5° .XX = 0.25°	MATERIAL: /	 2700 Mill Street, Unit 400, Reno, NV 89502	PART NUMBER: ECX-MPMP1-324P-XM-Y
	DESCRIPTION: MPO-MPO 24F Multimode OM3		Product name: connectivity
	DEBUR AND BREAK SHARP EDGES/CORNERS AT 0.2mm MAX	DRAWN BY: Jack	ORG DATE: 2021-07-20
	INTERPRET TO ASME Y14.100	APPROVED BY: Mike	REV DATE: 2021-07-20
UNITS: mm [in]	SIZE: A4	SCALE: 1 : 1	SHEET: 1/1
4	3	2	1