

Basic PDU

SKU#: EPB1J39K

The EPB1J39K basic rack PDU distributes power to devices in the rack with premium components. Labeled outlets allow easy identification for reduced connectivity errors. Designed and manufactured in the USA, this TAA-compliant rPDU provides the quality and value needed in the modern data center.

PRODUCT FEATURES

- TAA Compliant - Made in USA
- Premium components
- Ultra-low-profile design
- P-Lock compatible

APPLICATIONS

- Government and secure environments
- Colocation facilities
- MDF, IDF, data center, computer room, data room



SPECIFICATIONS

ELECTRICAL	SPECS
Acceptable Input Voltage	120/208V, +6%, -10%
Input Current (Phase)	20A (3-Phase, 16A derated)
Input Frequency	50/60 Hz
Input Power	5.7 kVA
Input Plug	L21-20P
Rated Output Current (Phase)	16A
Rated Output Current (Outlet)	C13: 12A, C19: 16A, N5: 12/16A
Overload Protection (Internal)	N/A
Outlet Configuration	Total: (24)C13, (12)C19, (3)N5-15/20R

PHYSICAL	SPECS
Dimensions	68" x 2.2" x 2.2" (1729 x 56 x 56 mm)
Depth at Circuit Breaker, in (mm)	2.2" (56mm)
Input Cord Length, ft (m)	10' (3m)

ENVIRONMENTAL	OPERATING	STORAGE
Maximum Elevation, Above MSL	10,000 ft / 3,000 m	50,000 ft / 15,000 m
Temperature	0 to 40 °C / 32 to 104 °F	0 to 60 °C / 32 to 140 °F
Humidity	5-95% RH non-condensing	5-95% RH non-condensing

COMPLIANCE/STANDARDS	SPECS
EMC Compliance	N/A
Safety Compliance	cCSAus to UL 62368-1
Environmental	RoHS
TAA Compliant	Yes

WARRANTY	Duration
PDU Warranty	Lifetime

