

EMT Compression Connectors and Couplings

Compression fittings provide a secure, vibration-resistant connection for EMT conduit systems. Ideal for applications requiring enhanced mechanical strength and electrical continuity.

Features & Benefits:

- Made from zinc-plated steel
- Superior corrosion resistance
- Application:
 - Connectors: Secure EMT conduit to steel outlet boxes or enclosures.
 - Couplings: Join two EMT conduit sections.
- Indoor use recommended.
- UL Listed
- Meets or exceeds ANSI/UL 514B and CSA 22.2 No 18.3-12



EMT Compression Connectors

Part Number	Trade Size		Approx. Weight Per 100 Pieces	
	(in.)	(mm)	(lbs.)	(kg)
MAR-EMTCC12	1/2	16	8.7	3.9
MAR-EMTCC34	3/4	21	11.6	5.3
MAR-EMTCC1	1	27	19.6	8.9
MAR-EMTCC114	1 ¼	35	30.8	14
MAR-EMTCC112	1 ½	41	39.3	17.8
MAR-EMTCC2	2	53	57.3	26
MAR-EMTCC212	2 ½	63	143.5	65.1
MAR-EMTCC3	3	78	169	76.6
MAR-EMTCC312	3 ½	91	216.4	98.2
MAR-EMTCC4	4	103	252.1	114.4



www.marathonbroadband.com

EMT Compression Connectors - Insulated

Part Number	Trade Size		Approx.Weight Per 100 Pieces	
	(in.)	(mm)	(lbs.)	(kg)
MAR-EMTCCI12	1/2	16	8.8	4
MAR-EMTCCI34	3/4	21	11.7	5.3
MAR-EMTCCI1	1	27	19.6	8.9
MAR-EMTCCI114	1 ¼	35	31.1	14.1
MAR-EMTCCI112	1 ½	41	39.7	18
MAR-EMTCCI2	2	53	57.8	26.2
MAR-EMTCCI212	2 ½	63	144.1	65.4
MAR-EMTCCI3	3	78	169.9	77.1
MAR-EMTCCI312	3 ½	91	217.5	98.7
MAR-EMTCCI4	4	103	253.3	114.9

EMT Compression Coupling

Part Number	Trade Size		Approx.Weight Per 100 Pieces	
	(in.)	(mm)	(lbs.)	(kg)
MAR-EMTCCOUP12	1/2	16	11.4	5.2
MAR-EMTCCOUP34	3/4	21	14.3	6.5
MAR-EMTCCOUP1	1	27	21	9.5
MAR-EMTCCOUP114	1 ¼	35	34.5	15.6
MAR-EMTCCOUP112	1 ½	41	43.8	19.9
MAR-EMTCCOUP2	2	53	67.3	30.5
MAR-EMTCCOUP212	2 ½	63	189.9	86.2
MAR-EMTCCOUP3	3	78	239.6	108.7
MAR-EMTCCOUP312	3 ½	91	281.1	127.5
MAR-EMTCCOUP4	4	103	323.7	146.8