


PVC Conduit Schedule 40 and Schedule 80

Marathon Schedule 40 and Schedule 80 conduit is designed for above ground and underground applications. The nonmetallic PVC material is rust proof and corrosion-resistant.

Features and Benefits:

- ETL Listed
- UL Listed
- Conforms to UL STD 651
- Conforms to CSA 22.2 211.0.03 and 211.2.06
- Available in 10' and 20' lengths
- Conduit end option is Bell End
- Sunlight Resistant
- Rated for use with 90°C wire
- Conduit color is Grey
- Internal smooth wall allows for easy pull-through for wires



Nonmetallic PVC Schedule 40 Conduit Bell End - 10 ft. Length

Part Number	Trade Size (in.)	Outside Diameter (OD) (in.)	Feet per Pack	Approximate Weight (lbs. / ft.)	Nominal ID (in.)
40156499410	1/2	0.832	6,000	0.169	0.851
40156499409	3/4	1.055	4,400	0.225	1.064
40156499438	1	1.323	3,600	0.330	1.329
40156499467	1-1/4	1.673	3,300	0.452	1.677
40156499466	1-1/2	1.902	2,250	0.538	1.918
40156499437	2	2.378	1,400	0.719	2.392
40156499465	2-1/2	2.882	930	1.153	2.890
40156499436	3	3.504	880	1.446	3.514
40156499464	3-1/2	3.976	630	1.808	4.014
40156499435	4	4.488	570	2.119	4.514
40156499434	5	5.551	380	2.932	5.592
40156499433	6	6.614	260	3.766	6.657
40156499420	8	8.625	180	5.512	8.638



www.marathonbroadband.com

Nonmetallic PVC Schedule 40 Conduit Bell End - 20 ft. Length

Wesco Part Number	Trade Size (in.)	Outside Diameter (OD) (in.)	Feet per Pack	Approximate Weight (lbs. / ft.)	Nominal ID (in.)
40156499408	¾	1.055	8,800	0.225	1.064
40156499432	1	1.323	7,200	0.330	1.329
40156499463	1-¼	1.673	6,600	0.452	1.677
40156499462	1-½	1.902	4,500	0.538	1.918
40156499431	2	2.378	2,800	0.719	2.392
40156499458	2-½	2.992	1,860	1.153	2.890
40156499430	3	3.504	1,760	1.446	3.514
40156499429	4	4.488	1,140	2.119	4.514
40156499428	5	5.551	760	2.932	5.592
40156499427	6	6.614	520	3.766	6.657

Nonmetallic PVC Schedule 80 Conduit Bell End - 10 ft. Length

Wesco Part Number	Trade Size (in.)	Outside Diameter (OD) (in.)	Feet per Pack	Approximate Weight (lbs. / ft.)	Nominal ID (in.)
40156499407	½	0.843	6,000	0.212	0.852
40156499406	¾	1.055	4,400	0.293	1.064
40156499426	1	1.323	3,600	0.432	1.330
40156499461	1-¼	1.673	3,300	0.607	1.677
40156499460	1-½	1.902	2,250	0.729	1.918
40156499425	2	2.378	1,400	0.970	2.393
40156499459	2-½	2.882	930	1.511	2.890
40156499424	3	3.504	880	2.024	3.513
40156499423	4	4.488	570	2.901	4.515
40156499422	5	5.563	380	3.968	5.593
40156499421	6	6.625	260	5.732	6.658

PRINT LINE EXAMPLE:

Marathon schedule 40 2" rigid PVC nonmetallic conduit above ground and underground sunlight resistant maximum 90°C wire conforms to ul std 651 cetus listed 29116900 78006006006 03152023.